

Amino 130

HD IP SET TOP BOX

Detailed Specification A130 - High Definition IP-STB

Size and weight	133mm x 180mm x 40mm. 480g (excluding accessories and packaging)
Inputs	Ethernet 10/100 BaseT via RJ-45 shielded connector
Outputs	HDMI 1.2a. with HDCP 10-way Mini-DIN for Composite video, Component (YPrPb), RGB, S-Video and analogue audio S/PDIF (optical). USB2.0 RF Loop through and Modulator
Power	5V DC at 1.5A via external power supply less than 8W typical usage (external supply input voltage 100-240V AC 50-60Hz, 0.8A max, output 5VDC 3A)
Codecs	MPEG-2 MP@HL MPEG-4 pt10 AVC/H.264 HP@L4
Video resolutions	Up to 720p and 1080i
Graphics resolutions	HD graphics up to 1280x720
Audio	Analogue stereo audio out. Stereo and Dolby 5.1 surround via S-PDIF and HDMI. Dolby Digital pass through to external decoder
Security	Wide selection of DRM and Conditional Access support. HDCP on HDMI Macrovision on SD outputs (option)
Memory	32MB Flash, 192MB RAM
Front panel	LEDs Power on /IR command received (Red)
Operating environment	ETS 300-019-1-3 Class 3.1
EMC conformance	FCC Part 15 class B. 2004/108/EC EN55022
Safety approvals	CAN/ CSA-C22.2 No. 60065-03 EN60065
RoHS	2002-95-EC
WEEE	2002-96-EC
Operating temperature	0°C (32°F) to 40°C (104°F)
Storage humidity	5% to 95% RH (non-condensing)

