

MTX 715x



Features

IP SET TOP BOX

Support SD and HD

System:

- 256 MB DDR II Memory
- 128 MB NAND Flash Memory, expandable to 256MB
- 4k EEPROM

Front Panel :

- Front Panel with colours LED. (Power, IR, Link, HDD-if installed)
- IR Receiver
- RF4CE module (Reserved by optional)
- GPIO pin (reserved for VFD by optional)
- One USB 2.0

Rear Panel Outlets :

- Power Switch
- DC 12V in
- One USB 2.0
- One RJ-45 Ethernet (10/100)
- One SPDIF (Optical)
- Audio L/R (RCA)
- Video CVBS (Composite)
- Components (YPbPr)
- HDMI (with HDCP)
- One Smart Card Reader(Module, Optional)
- One SATA internal (on board Optional if HDD required)
- One Tuner NIM module (on board optional for DVB-T/C, ATSC)
- RF In and RF Out (F-connector or IEC , optional with Tuner)

Options:

- mPCI (for Wireless module)
- Form Factor:
- Small one (eBox one), Keep same Front panel, Rear Panel with a new one

Power Unit:

- DC/DC on board
- External Power Adapter 90-260V AC in, 50/60 Hz, DC 12V , 1.5A output

Accessories:

- User Manual (A5, pages depends)
- Ethernet cable 1.5m (Grey)
- RCA cable 1.5m (Red, white, yellow)
- HDMI cable 1.5m (Black, Optional)

Packaging:

- Printing on white box
- With Power cord, Adapter, Manuals, Remote Control(with Battery), and Ethernet cables, RCA cable (Optional for HDMI cable)